





型号 Part No	内径 Internal Diameter			外径 External Diameter			法兰外径 Flang ΦD <sub>r</sub>	高度 Length
	内径 d	装配轴径 Shaft-Φd <sub>s</sub>	装配后内孔尺寸 Φd <sub>i</sub> (H9)	外径 D	装配座孔 Housing-ΦD <sub>H</sub>	理论外径公差 O.D.ΦD <sub>t</sub>		ID<80L±0.25
								ID>80L±0.25
CNB090F/092F 5030	50	49.975 49.936	50.062 50.000	55	55.025 55.000	+0.085 +0.045	65	30
CNB090F/092F 5035								35
CNB090F/092F 5040								40
CNB090F/092F 5050								50
CNB090F/092F 5530	55	54.970 54.924	55.074 55.000	60	60.030 60.000		70	30
CNB090F/092F 5535								35
CNB090F/092F 5540								40
CNB090F/092F 5550								50
CNB090F/092F 6030	60	59.970 59.924	60.074 60.000	65	65.030 65.000		75	30
CNB090F/092F 6035								35
CNB090F/092F 6040								40
CNB090F/092F 6050								50
CNB090F/092F 6060	65	64.970 64.924	65.074 65.000	70	70.030 70.000		80	60
CNB090F/092F 6530								30
CNB090F/092F 6535								35
CNB090F/092F 6540								40
CNB090F/092F 6550	70	69.970 69.924	70.074 70.000	75	75.030 75.000		85	50
CNB090F/092F 6560								60
CNB090F/092F 7035								30
CNB090F/092F 7040								35
CNB090F/092F 7050	75	74.970 74.924	75.074 75.000	80	80.030 80.000		90	40
CNB090F/092F 7060								50
CNB090F/092F 7070								60
CNB090F/092F 7535								35
CNB090F/092F 7540	80	79.970 79.924	80.074 80.000	85	85.030 85.000		100	40
CNB090F/092F 7550								50
CNB090F/092F 7560								60
CNB090F/092F 7570								70
CNB090F/092F 8040	90	89.960 89.910	90.087 90.000	100	100.035 100.000		110	40
CNB090F/092F 8050								50
CNB090F/092F 8060								60
CNB090F/092F 8070								70
CNB090F/092F 8080	90	89.960 89.910	90.087 90.000	100	100.035 100.000		110	80
CNB090F/092F 9050								50
CNB090F/092F 9060								60

型号 Part No	内径 Internal Diameter			外径 External Diameter			法兰外径 Flang ΦD <sub>r</sub>	高度 Length
	内径 d	装配轴径 Shaft-Φd <sub>s</sub>	装配后内孔尺寸 Φd <sub>i</sub> (H9)	外径 D	装配座孔 Housing-ΦD <sub>H</sub>	理论外径公差 O.D.ΦD <sub>t</sub>		ID<80L±0.25
								ID>80L±0.25
CNB090F/092F 9070	95	94.964 94.910	95.087 95.000	100	100.035 100.000	+0.120 +0.070	115	70
CNB090F/092F 9080								80
CNB090F/092F 9090								90
CNB090F/092F 10050	100	99.964 99.910	100.087 100.000	105	105.035 105.000		120	50
CNB090F/092F 10060								60
CNB090F/092F 10070								70
CNB090F/092F 10080								80
CNB090F/092F 10090								90
CNB090F/092F 11050								110
CNB090F/092F 11060	60							
CNB090F/092F 11070	70							
CNB090F/092F 11080	80							
CNB090F/092F 11090	90							
CNB090F/092F 12060	120	119.964 119.910	120.087 120.000	125	125.035 125.000		140	60
CNB090F/092F 12070								70
CNB090F/092F 12080								80
CNB090F/092F 12090								90
CNB090F/092F 13060	130	129.957 129.894	130.100 130.000	135	135.040 135.000		155	60
CNB090F/092F 13070								70
CNB090F/092F 13080								80
CNB090F/092F 13090								90
CNB090F/092F 14060	140	139.957 139.894	140.100 140.000	145	145.040 145.000		165	60
CNB090F/092F 14070								70
CNB090F/092F 14080								80
CNB090F/092F 14090								90
CNB090F/092F 15060								150
CNB090F/092F 15070	70							
CNB090F/092F 15080	80							
CNB090F/092F 15090	90							
CNB090F/092F 16060	160	159.957 159.894	160.100 160.000	165	165.040 165.000		190	60
CNB090F/092F 16070						70		
CNB090F/092F 16080						80		
CNB090F/092F 16090						90		
CNB090F/092F 17060	170	169.957 169.894	170.100 170.000	175	175.040 175.000	200	60	
CNB090F/092F 17070							70	



型号 Part No	内径 Internal Diameter			外径 External Diameter			法兰外径 Flang ΦD <sub>f</sub>	高度 Length
	内径 d	装配轴径 Shaft-Φd <sub>s</sub>	装配后内孔尺寸 Φd <sub>i</sub> (H9)	外径 D	装配座孔 Housing-ΦD <sub>H</sub>	理论外径公差 O.D.ΦD <sub>t</sub>		ID<80L±0.25
								ID>80L±0.25
CNB090F/092F 17080	170	169.957	170.100	175	175.040	+0.210 +0.130	200	80
CNB090F/092F 17090		169.894	170.000		175.000			90
CNB090F/092F 18060	180	179.957 179.894	180.100 180.000	185	185.040 185.000		215	60
CNB090F/092F 18070								70
CNB090F/092F 18080								80
CNB090F/092F 18090								90
CNB090F/092F 19060	190	189.950 189.878	170.100 170.000	195	195.046 195.000		225	60
CNB090F/092F 19070								70
CNB090F/092F 19080								80
CNB090F/092F 19090								90
CNB090F/092F 20060	200	199.950 199.878	200.115 200.000	205	205.046 205.000		235	60
CNB090F/092F 20070								70
CNB090F/092F 20080								80
CNB090F/092F 20090								90
CNB090F/092F 22560	225	224.950 224.878	225.115 225.000	230	230.046 230.000		260	60
CNB090F/092F 22570								70
CNB090F/092F 22580								80
CNB090F/092F 22590								90
CNB090F/092F 25060	250	249.950 249.878	250.115 250.000	255	255.046 255.000		290	60
CNB090F/092F 25070								70
CNB090F/092F 25080						80		
CNB090F/092F 25090						90		
CNB090F/092F 26560	265	264.955 264.893	265.130 265.000	270	270.052 270.000	305	60	
CNB090F/092F 26570							70	
CNB090F/092F 26580							80	
CNB090F/092F 26590							90	
CNB090F/092F 28560	285	284.944 284.863	285.130 285.000	290	290.052 290.000	325	60	
CNB090F/092F 28570							70	
CNB090F/092F 28580							80	
CNB090F/092F 28590							90	
CNB090F/092F 30060	300	299.944 299.863	300.130 300.000	305	305.052 305.000	340	60	
CNB090F/092F 30070							70	
CNB090F/092F 30080							80	
CNB090F/092F 30090							90	